

HIGH PRESSURE WATER BLASTING GUNS

ELECTRICAL

12.H.5 – 03/2023



SP 3200 E

- Hand grip made of high impact resistant plastic.
- Stainless steel connection housing for lance and high pressure hose.
- Front hand grip, swivel position adjustable.
- Built-in Reed switch, for intrinsically safe circuit Ex (i) 24 Volt control signal.
- Safety catch in safety lever.
- With the safety lever over 80 % less strength is required to operate and hold the trigger compared to conventional guns.

TECHNICAL DATA SP 3200 E

Operating pressure max.:	3200 bar
Flow rate at Δp 5 bar max.:	30 l/min
<u>Connection thread</u>	
Pressure screw:	M26 x 1.5 male
Pressure ring:	M14 x 1.5 LH female
Length (750 mm lance):	1005 mm
Connection thread (lance):	M14 x 1.5 LH
Weight (750 mm lance):	3.4 kg



If the reaction force is over 150 N (up to max. 250 N) then the jetting tool must be fitted with a support device such as a shoulder stock!

Type	Length of lance	Code no.
SP 3200 E	750 mm	00.03141.0035
	1000 mm	00.03141.0044
	1300 mm	00.03141.0048

ACCESSORY (optional)	Code no.
SPRAY BACK SHIELD for the above model Ø 280 mm Weight: 0.300 kg	00.04877.0014

HAMMELMANN®