HIGH PRESSURE WATER BLASTING GUNS TWO HAND OPERATION

ELECTRICAL



SP 3200 E - 2H

- For electrical operation.
- Hand grip made of high impact resistant plastic.
- Stainless connection housing for lance and high pressure hose.
- Front hand grip, swivel position adjustable with additional electric contact.
- Built-in Reed switch, for intrinsically safe circuit Ex (i) 24 Volt control signal.

TECHNICAL DATA SP 3200 E - 2H

	750 mm lance	1000 mm lance
Operating pressure max.:	3200 bar	
Flow rate at ∆p 5 bar max.:	30 l/min	
Connection thread]	
Pressure screw:	M26 x 1.5 male	
Pressure ring:	M14 x 1.5 LH female	
Length:	1005 mm	1255 mm
Connection thread (lance):	M14 x 1.5 LH	
Weight:	5.0 kg	5.3 kg



If the reaction force is over 150 N (up to max. 250 N) then the jetting tool must be fitted with a support device such as a shoulder stock!

Туре	Length of lance	Code no.
SP 3200 E - 2 H - 750	750 mm	00.03141.0061
SP 3200 E - 2 H - 1000	1000 mm	00.03141.0081

Accessory (optional)	Code no.
SPLASH PROTECTION Weight: 0.210 kg	00.04877.0017

