## HIGH PRESSURE WATER BLASTING GUNS TWO HAND OPERATION MECHANICAL BYPASS



## SP 3000 MB - 2H

- For mechanical 2-hand operation.
- 2 bypass valves operated by the triggers directly at the gun.
- Hand grips made of high impact resistant plastic.
- Stainless steel housing.
- Front hand grip, swivel position adjustable, with additional bypass valve.
- · Safety catch in the safety lever.
- With the safety lever over 80 % less strength is required to operate and hold the trigger compared with conventional guns.



If the reaction force is over 150 N (up to max. 250 N) then the jetting tool must be fitted with a support device such as a shoulder stock!

## TECHNICAL DATA SP 3000 MB - 2H

Operating pressure max.:	3000 bar
Flow rate at ∆p 5 bar max.:	30 l/min
Connection thread	
Pressure screw:	M26 x 1.5 male
Pressure ring:	M14 x 1.5 LH female
Length (750 mm lance):	1380 mm
Connection thread (lance):	M14 x 1.5 LH
Weight (750 mm lance):	6.5 kg

Туре	Length of lance	Code no.
SP 3000 MB - 2H	750 mm	00.03141.0074

Accessory (optional)	Code no.
SPLASH PROTECTION Weight: 0.210 kg	00.04877.0017

